ELSEVIER

Contents lists available at ScienceDirect

Applied Catalysis B: Environmental

journal homepage: www.elsevier.com/locate/apcatb



Rational design and fabrication of multifunctional catalyzer Co₂SnO₄-SnO₂/GC for catalysis applications: Photocatalytic degradation/catalytic reduction of organic pollutants



Jianhua Zheng, Lei Zhang*

College of Chemistry, Liaoning University, 66 Chongshan Middle Road, Shenyang, Liaoning, 110036, People's Republic of China

ARTICLE INFO

Keywords: Co₂SnO₄-SnO₂/GC Heterojunctions catalyst Photocatalytic degradation Catalytic reduction Organic contaminant

ABSTRACT

Hollow porous Co_2SnO_4 -Sn O_2 /graphite carbon (Co_2SnO_4 -Sn O_2 /GC) nanocube heterojunction was designed and constructed as advanced catalytic material by calcining $CoSn(OH)_6$ precursors followed an immersion carbon coating (using the recyclable napkin as graphite carbon source) and calcinations treatment. The design methods focus on forming intimate interfacial contacts among Co_2SnO_4 , SnO_2 and GC (in situ hybridization of the composite). The obtained Co_2SnO_4 -Sn O_2 /GC exhibits remarkable dual catalytic behavior including the high catalytic efficiency for photocatalytic (under visible light) degradation of chlorotetracycline (CTC)/tetracycline (TC) and catalytic reduction of p-nitrophenol (p-NP). Co_2SnO_4 -Sn O_2 /GC could be recycled more than four times, preserving its activity and stability based on graphite carbon protective layer on the surface of catalysts. Owing to multiple heterojunctions structure features and the synergistic effects of different junctions, greatly enhance the charge carrier generation and suppress the charge recombination of electron-hole pairs, which would be beneficial to improve its catalytic activity. The possible mechanisms for the dual-functional catalytic reactions for organic contaminants over Co_2SnO_4 -Sn O_2 /GC were made a thorough inquiry. This study not only shows a possibility for the utilization of low cost the recyclable napkin as a substitute for graphene but also provides a new insight into the design and construction of new heterojunction catalysts for enhancing catalytic activity.

1. Introduction

Antimicrobial agents released in the environment such as chlorotetracycline (CTC) and tetracycline (TC), are more difficult to be degraded by bio-treatment and common physicochemical methods because of theirs high chemical stability, which can seriously pose a threat to most of living organisms. Moreover, *p*-nitrophenol (*p*-NP) is one of most notorious industrial organic contaminants possessing carcinogenic character and high toxicity. At present, most of the antimicrobial agents and nitrophenol have been listed as priority pollutants [1,2]. It is no doubts that decomposing contaminants to nontoxic species or transforms to reusable compounds will be a satisfying strategy of remediation for such contaminants. One effective way to solve this problem is to develop multifunctional catalysts with high catalytic activity. Thus, the search for novel catalytic materials for decomposing (effectively transforms) pollutants to nontoxic (reusable) species is urgently needed [3–5].

Stannate bimetal oxides like Zn_2SnO_4 [6–10], $BaSnO_3$ [11–15], Cd_2SnO_4 [16], and Co_2SnO_4 [17], have been widely studied and developed for various applications such as solar cells, gas sensors, Li-ion

batteries, photocatalysts, due to their high theoretical capacity, low cost and ease of availability. So far, composite heterostructures of stannate bimetal oxides including Ag@AgCl/Zn₂SnO₄ [18], Zn₂SnO₄/grapheme [19], Zn₂SnO₄/ZnO [20], Zn₂SnO₄-carbon [21], Mn₃O₄/Zn₂SnO₄ [22], Co₂SnO₄-multiwalled carbon [23], CoSnO₃@Co₃O₄ [24], and CoSnO₃@C [25], have been reported to show a superior photoelectric behavior compared to pure stannate-based bimetal oxides. However, above-mentioned composites were usually constructed through multiple steps by separately preparing the different materials and then blending them by coating route. Development of a facile and environmentally friendly method for incorporating the different components into a composite would be greatly beneficial for enhancing photoelectric performances of heterostructures materials. Among the Stannate-based bimetal oxides, spinel Co₂SnO₄ has been proven to be a highly promising performers for its small band gap and high electron mobility [26,27], To date, there are very few reports on the photodegradation and the catalytic reduction of contaminants using Co₂SnO₄composites as multifunctional catalysts.

In this paper, an effective strategy has been proposed to papered 3D hollow $\text{Co}_2\text{SnO}_4\text{-SnO}_2/\text{GC}$ nanocube by a facile, inexpensive, relative

E-mail address: zhanglei63@126.com (L. Zhang).

^{*} Corresponding author.

green and eco-friendly synthetic route. In particular, in situ growth SnO_2 and Co_2SnO_4 can well incorporate each other and create the intimate contact in the heterojunction region, assuring rapid migration of electrons from the Co_2SnO_4 to SnO_2 , which can greatly accelerate carriers transfer and improve charge separation efficiency [28], The obtained Co_2SnO_4 - SnO_2 /GC exhibited superior catalytic performance and the excellent stability.

2. Experiment section

2.1. Materials

 $SnCl_4{:}5H_2O,\ CoCl_2{:}6H_2O,\ and\ NaOH$ are of analytical grade and were obtained from Sinopharm Chemical Reagent Co., Ltd. (China). Chlorotetracycline (CTC), Tetracycline (TC) and p-nitrophenol (p-NP) were purchased from Shanghai Shunbo Biological Engineering Co. Ltd. whereas the napkin was collected from the local restaurants.


2.2. Preparation of various catalysts

2.2.1. Synthesis of hollow CoSnO₃ nanocube

In a typical synthesis, $15\,\mathrm{mL}$ of ethanol solution of $\mathrm{SnCl_4'6H_2O}$ (3 mmol) was added to the mixture dissolving $\mathrm{CoCl_2'6H_2O}$ (3 mmol) and $\mathrm{C_6H_5Na_3O_7'2H_2O}$ (3 mmol) under stirring. Consecutively, $15\,\mathrm{mL}$ 2.0 $\mathrm{mol\,L^-}$ NaOH was added drop by drop to the mixture under stirring. After $1.5\,\mathrm{h}$, $60\,\mathrm{mL}$ 8.0 $\mathrm{mol\,L^-}$ NaOH was added gradually into above mixture. The obtained precipitant was rinse-centrifugation with deionized water and ethanol for several times until to remove excess NaOH and then annealed in $\mathrm{N_2}$ flow at 500 °C for $2\,\mathrm{h}$ with a slow ramp rate of $2\,\mathrm{^{\circ}C}$ min $^{-1}$.

2.2.2. Synthesis of Co₂SnO₄-SnO₂/GC

Firstly, the napkin was cleaned with by immersion in a mixture of ethanol and deionized water (1:1, v/v) for 12 h and dried at 80 °C. Secondly, the cleaned napkin was immersed in deionized water with stirring vigorously to obtain pulp and then dried at 105 °C. Afterwards, 0.50 g as-prepared $CoSnO_3$ was dispersed in 30 mL deionized water containing 0.05 g as-prepared pulp, sonicated for 60 min and magnetic stirred for 12 h under ambient conditions to form a homogeneous solution and then the water was evaporated. The pulp will spontaneously coat on the $CoSnO_3$ NPs and the obtained product was dried at 100 °C over night. Finally, the sample was carbonized in N_2 flow at 600 °C for 3 h. Co_2SnO_4 - SnO_2 was fabricated without adding napkin using the same process. The process of fabrication is illustrated in the Scheme 1. Additionally, the pure Co_2SnO_4 and SnO_2 were obtained by simple co-



Scheme 1. Schematic illustration of the preparation process of Co₂SnO₄-SnO₂/GC.

precipitation method according to literatures [29,30].

2.3. Characterization

The powder X-ray diffraction with Cu Ka radiation (XRD, D/max-2200, Rigaku, Japan) was used to determine the crystal structure and purity of samples. Raman spectra were performed using Laser Confocal Micro-Raman Spectroscope (LabRAM Aramis). BET specific surface area and N_2 adsorption-desorption isotherms of samples were measured at 77 K using a surface area analyzer (BET Autosorb-iQ, American). Morphology of the samples was characterized by a field emission scanning electron microscope (SEM, S4800, Hitachi Co., Japan). TEM was taken on a transmission electron microscope (TEM, 2100F, JEOL Co., Japan). X-ray photoelectron spectroscopic (XPS) measurement was performed on a Thermo Electron Corporation ESCALAB 250 Xi. UV-vis diffuse reflectance spectra (DRS) were performed with an UV-vis spectrophotometer (Shimadzu, UV-2600 Japan) equipped with an integrating sphere diffuse reflectance accessory.

2.4. Catalytic activities

2.4.1. Photocatalytic activities test

The typical antibiotic CTC/TC was used to evaluate the photocatalytic activities. Typically, the as-prepared catalyst (40 mg) was dispersed in $10~{\rm mg\,L^{-1}}$ of CTC/TC aqueous solution (100 mL). Then the suspension was magnetically stirred for 60 min in the dark to obtain adsorption-desorption equilibrium. Subsequently, the suspension of catalyst and CTC/TC was irradiated by a 500 W xenon lamp with a 420 nm cutoff filter. During the process, about 3 mL suspension was collected at an interval of 20 min and centrifugalizes to remove the catalyst. The concentration of CTC/TC was recorded by the UV–vis spectrophotometer.

2.4.2. Free radical trapping tests

The process is the same as photocatalytic activity test mentioned above except adding corresponding scavengers. Experimentally, 0.5 mM sodium oxalate (Na₂C₂O₄, h⁺), and 5 mM *tert*-Butanol (T-BuOH, •OH) were utilized for scavengers [31,32]. The addition of N₂/O₂ was bubbled to clarify whether generation of \cdot O₂⁻ (e⁻ + O₂ \rightarrow •O₂⁻) [33] in the photocatalytic reaction.

2.4.3. Catalytic reduction test

Typically, $10~{\rm mg}~{\rm L}^{-1}$ of p-NP aqueous solution (50 mL) and 2 mL of freshly prepared aqueous NaBH₄ (0.1 mol L⁻) were successively added into a 100 mL beaker, and then 20 mg catalyst was added into reaction system with stirring constantly. The concentration of p-NP was measured by the UV–vis spectrophotometer.

3. Results and discussion

3.1. Catalyst characterization

Scanning electron microscopy (SEM) and transmission electron microscopy (TEM) were applied to confirm the morphology and detailed structure of the as-obtained products. The pure CoSnO₃ displays well-defined nanocube morphologies with a diameter of ca. 200–220 nm (Fig. 1a). As shown in TEM image, the feature of hollow for the nanocube can be clearly observed (inset of Fig. 1a). The cubeshell thickness of CoSnO₃ is about 50 nm. The Co₂SnO₄-SnO₂ was obtained after annealing the CoSnO₃ at 600 °C. As Fig. 1b exhibited, Co₂SnO₄-SnO₂ well reserves the nanocube shape with an average diameter of ca. 240 nm. The surface of Co₂SnO₄-SnO₂ becomes rougher comparing with that of CoSnO₃. The TEM image confirms that the cavity dimension becomes smaller, exhibiting the general appearance of hierarchical porous (inset of Fig. 1b). The changes can be attributed to the phase change from CoSnO₃ to mixed Co₂SnO₄ and SnO₂ hybrid.




Fig. 1. (a–c) SEM images of $CoSnO_3$, Co_2SnO_4 - SnO_2 and Co_2SnO_4 - SnO_2 /GC, respectively (d) high-magnification SEM images (e) TEM image and (f) HRTEM image of Co_2SnO_4 / SnO_2 /GC composite. Inset: TEM of (a) $CoSnO_3$, (b) Co_2SnO_4 - SnO_2 and (c) Co_2SnO_4 - SnO_2 /GC, respectively. (For interpretation of the references to colour in the text, the reader is referred to the web version of this article.)

Fig. 1c is the typical SEM image of Co₂SnO₄-SnO₂/GC hybrid, it can be seen that the Co₂SnO₄-SnO₂ nanocube is homogeneously encapsulated by carbon layer (magnified image Fig. 1d, indicated by the red circles) with an average diameter of about 260 nm. As the TEM image displayed (inset of Fig. 1c), the hollow porous structure is maintained well without noticeable change. The Co₂SnO₄-SnO₂ is tightly coated with flake-like GC, revealing to form the Co₂SnO₄-SnO₂/GC ternary heterojunction hybrid. To further elucidate the nanostructure of Co₂SnO₄-SnO₂/GC, the HRTEM analysis has been performed. The lattice fringes with different distances can be observed in (Fig. 1e). The interplanar spacing of 0.49 nm corresponds to (111) lattice planes of Co₂SnO₄. Analogously, the interplanar distances of lattice fringes calculated to be 0.34 nm and 0.26 nm are attributable to (110) and (101) planes of SnO₂, respectively. Moreover, some intersections of the lattice fringes can be found in Fig. 1e (indicated by the circles), further implying that an intimate contact is formed between SnO2 and Co2SnO4.

The surface areas and pore structures of Co_2SnO_4 - SnO_2 and Co_2SnO_4 - SnO_2 /GC were characterized by N_2 adsorption-desorption isotherms. Both samples are of type IV (Fig. 1f), suggesting the existence of mesoporous in the samples. The specific surface area and cumulative pore volume of samples are listed in inset of Fig. 1f. Clearly, the BET of Co_2SnO_4 - SnO_2 /GC (50.67 m² g⁻¹) is larger than that corresponding value for Co_2SnO_4 - SnO_2 (30.56 m² g⁻¹). The large BET surface area with more active sites is possible to enhancement of the

catalytic activity [34].

The powder X-ray diffraction (XRD) was carried out to insight the crystallinity and phase information of as-obtained Co2SnO4-SnO2 and Co₂SnO₄-SnO₂/GC composite, as displayed in Fig. 2a. The characteristic diffraction peaks located at 17.78 (111), 29.20 (220), 34.40 (311), 35.99 (222), 41.79 (400), 55.22 (511), 60.59 (440), and 71.58 (533), which are assigned to Co₂SnO₄ (JCPDS No. 29-0514) [35]. The main diffraction peaks observed at 20 values of 26.61 (110), 33.89 (101), 37.95 (200), 51.78 (211), 54.76 (220), 61.87 (310), 64.72 (112) and 65.94 (301) can be easily indexed to SnO₂ (JCPDS No. 41-1445) [36]. In addition, there is no other diffraction peaks corresponding to the low-valence ions (Sn₂O₃) [37]. The CoSn(OH)₆ is thermodynamically unstable. Thus, CoSnO₃ is obtained by thermal-induced dehydration of $CoSn(OH)_6$ ($CoSn(OH)_6 \rightarrow CoSnO_3 + 3H_2O$) during the annealed process. After carbon source is introduced, Co₂SnO₄-SnO₂/GC hybrid was obtained after annealing in N2 at 600 °C. The synthetic method can Co₂SnO₄ and SnO_2 to hybridize (2CoSnO₃ → Co₂SnO₄ + SnO₂). Notably, after introduction of carbon, new characteristic diffraction peaks appeared at about 26.60° (inset of Fig. 2a), 44.67° and 50.82° in the XRD pattern of Co₂SnO₄-SnO₂/GC, which are well indexed to the (002), (101) and (102) peaks of graphite carbon (JCPDS No. 99-0057) [38]. The results of XRD are consistent with HRTEM patterns.

To further confirm the presence of graphitic carbon, the final




Fig. 2. (a) XRD patterns of samples, (b) XPS of Co₂SnO₄-SnO₂/GC, (c) Co-2p, (d) Sn-3d, (e) O-1s and (f) C-1s, respectively. Inset of (b) Raman spectra of Co₂SnO₄-SnO₂/GC.

 $\text{Co}_2\text{SnO}_4\text{-SnO}_2/\text{GC}$ products was investigate using Raman spectrum (inset of Fig. 2b). Two main peaks are observed at 1582.63 (G-band) and 1344.58(D-band) cm $^{-1}$ and the intensity ratio of the G band to the D band (I_G/I_D) was calculated as 0.57, demonstrating the existence of graphite sp 2 carbon and disordered sp 3 carbon, respectively [39].

X-ray photoelectron spectroscopy (XPS) was carried out to confirm the valent state of elements in Co₂SnO₄-SnO₂/GC. The survey XPS spectrum suggests the predominant presence of Co, Sn, O, and C elements, and no other heteroelements were detected (Fig. 2b). The highresolution XPS spectrum of Co is shown in Fig. 2c. The peaks of Co 2p_{3/} $_{2}$, Co $2p_{1/2}$ orbital of diatomic cobalt ions are observed at 781.48 and 797.56 eV with the shake-up satellite (denoted as Sta.) structure at 786.51 and 803.25 [40]. As Fig. 2d shown, the Sn 3d region exhibits two main characteristic peaks, which can be further deconvoluted into two sets of peaks with a spin-orbit splitting energy of ca. 8.6 eV. The peaks separation value corresponds to a binding energy of Sn4+ [41-43], the peaks centered at 495.63 and 487.05 eV can be ascribed to Sn⁴⁺ of SnO₂ [44]; while the others two peaks denoted as 494.43 and 485.83 eV are attributed to Sn⁴⁺ of Co₂SnO₄, respectively [17,45]. No peaks centered at 494.9 and 486.4 eV with a spin-orbit splitting energy of ca. 8.5 eV was observed, indicating the absence of the chemical state of Sn²⁺ (Sn₂O₃) in Co₂SnO₄-SnO₂/GC hybrid [37]. The O1s spectrum (Fig. 2e) shows three oxygen contributions (529.86 eV, 531.36 and 532.77). The two peaks at 529.86 and 531.36 eV attribute to metaloxygen bonds (Co-O and Sn-O), while another peak at 532.77

corresponds to –OH [46]. In addition, no peak located at 531.2 eV was observed, which is assigned to the oxygen vacancies [47–49], implying no oxygen vacancies formation under N_2 atmosphere in 600 °C. It is further demonstrate that SnO_2 and Co_2SnO_4 are coexistence in the hybrid system, which is well consist with the XRD analysis. In Fig. 2f, we can find three peaks with the binding energies of 284.62, 285.60 and 288.46, which correspond to reference C–C, C–O and O=C–OH, respectively [50]. The XPS results confirm the successful synthesis of Co_2SnO_4 - SnO_2 /GC hybrid system.

A serious of experiment including electrochemical impedance spectroscopy (EIS), and photoelectrochemical measurements were carried out to further clarify the hybrid system could enhance the charge transfer and inhibit the recombination of charge-pairs. A smaller diameter indicates a better electronic conductivity and charge transfer performance [51]. Fig. 3a displays EIS Nyquist plots of SnO₂, Co₂SnO₄, Co₂SnO₄-SnO₂, and Co₂SnO₄-SnO₂/GC. It is found that the Co₂SnO₄-SnO₂/GC has a smaller semicircle diameter comparing with SnO₂, Co₂SnO₄ and Co₂SnO₄-SnO₂. The lowest electron transfer resistance attribute to existence heterojunction of Co₂SnO₄, SnO₂ and GC, which helps to improve the efficiency of e⁻/h⁺ pair's separation, making it as a promising catalytic material [52]. The transient photocurrent responses of samples were recorded for four on-off cycles under visiblelight irradiation (Fig. 3b). Enhanced photocurrent intensity is observed for Co₂SnO₄-SnO₂/GC compared to Co₂SnO₄-SnO₂, indicating the synergistic effects of Co₂SnO₄-SnO₂ and carbon layer in the hybrid system




Fig. 3. (a) EIS Nyquist plots at 0.1 V bias potential vs. Ag/AgCl and (b) the periodic on/off photocurrent response at 0.2 V bias potential vs. Ag/AgCl of different samples. (0.1 mol L⁻¹ Na₂SO₄ aqueous solution under visible-light irradiation).




Fig. 4. (a) UV-vis diffuse reflectance spectra of samples (b) their corresponding plots of $(ahv)^{1/2}$ vs. photon energy and (c) the Mott-Schottky plots.




Fig. 5. (a) Photocatalytic degradation of CTC of different samples under visible-light irradiation, (b) the corresponding first-order plots, (c) photocatalytic degradation of TC under visible-light irradiation, and (d) the corresponding first-order plots over different samples.

achieved more efficiently inhibits the recombination of charge-pairs and accelerate rapid charge transfer through $\text{Co}_2\text{SnO}_4\text{-SnO}_2/\text{GC}$ heterojunction [53,54].

Fig. 4a shows UV-vis diffuse reflectance spectra of SnO₂, Co₂SnO₄,

Co₂SnO₄-SnO₂, and Co₂SnO₄-SnO₂/GC. It is clear from UV–vis DRS that Co₂SnO₄-SnO₂/GC hybrid exhibits higher light absorption property under visible light range, due to the interaction between Co₂SnO₄-SnO₂ and graphite carbon in the composites. The enhanced light harvesting




Fig. 6. (a) m/z of the degraded CTC and (b) the proposed main intermediates of the photodegradation of CTC, irradiation by visible light for 80 min.




Fig. 7. (a) Catalytic reduction p-nitrophenol and (b) the kinetics plots of p-nitrophenol reduction over different samples (20 mg catalysts, 50 mL p-NP 10 mg L⁻¹).




Fig. 8. (a) Cycling experiments for the different reactions by the prepared Co₂SnO₄-SnO₂/GC, and (b) The XRD patterns of Co₂SnO₄-SnO₂/GC before and after cyclic test.

implies that the hybrid catalyst could utilize more visible light. The derived band gaps can be obtained by the Kubelka-Munk theorem (Fig. 4b). The obtained corresponding band gap values for samples are 3.81 eV (SnO₂), 1.75 eV (Co₂SnO₄), 1.99 eV (Co₂SnO₄-SnO₂), and 1.85eV (Co₂SnO₄-SnO₂/GC). The Mott-Schottky (M-S) method is employed to elucidate the band energy potentials. As the Fig. 4c shown, the flat band potential (E_{FB}) potentials of Co_2SnO_4 and SnO_2 could be confirmed to be -0.58 (-0.34 eV vs. NHE) and -0.37eV (-0.13 eV vs. NHE), respectively. SnO2 and Co2SnO4 are n-type semiconductors owing to the positive slope of 1/C² versus potential curve, with the conduction band (E_{CB}) position 0.1-0.3 eV higher than that of E_{FB} [55,56]. Herein, the E_{CB} of Co_2SnO_4 and SnO_2 were determined to be -0.44 and -0.23 eV, respectively. Moreover, the valence band (E_{VB}) can be obtained by the formula $E_{VB} = E_{CB} + E_{g}$. Therefore, the corresponding E_{VB} of Co_2SnO_4 and SnO2 will occur at about 1.31 and 3.58 eV, respectively.

3.2. Activity measurements of Co₂SnO₄-SnO₂/GC


3.2.1. Photocatalytic activity


The photocatalytic performance of Co_2SnO_4 - SnO_2 /GC hybrid was evaluated by degradation of CTC under visible light irradiation. The degree of the photocatalysis is presented by the ratio of the concentration C/C_0 under various times. Fig. 5a exhibits diagram of the degradation of CTC using different catalysts. Obviously, direct decomposing of CTC under visible light irradiation could be neglected over SnO_2 , owing to its lack of response to visible light. It can be clearly observed that pure Co_2SnO_4 and Co_2SnO_4 - SnO_2 decomposed 32% and 63% TCT, respectively; while the removal efficiency of CTC reaches to about 83% over Co_2SnO_4 - SnO_2 /GC.

The inset of Fig. 5a shows the changes of absorbance of CTC over $\text{Co}_2\text{SnO}_4\text{-SnO}_2/\text{GC}$. Clearly, the intensity of the characteristic peak

decreases with the increase of visible light illumination time. A linear relation of $-\ln(C/C_0)$ vs reaction time was obtained, suggesting that the reaction can be considered as a pseudo-first-order reaction (Fig. 5b). The corresponding apparent kinetic rate constant (k) value of Co₂SnO₄-SnO₂/GC is estimated to be 0.017 min⁻¹, which is over 5.7 and 2.2 times higher than that of Co_2SnO_4 (0.003 min⁻¹) and Co_2SnO_4/SnO_2 (0.008 min⁻¹). Subsequently, the photocatalytic decomposing pathways for CTC were investigated by MS. From the mass spectra, the main m/z peaks located at 444, 362, 318, 274, 246, 194, 177, 167, 163, 148, 135, 121, 102, 92, and 74 were observed (Fig. 6a). The main intermediate with m/z value of 444 corresponds to CTC (m/z = 515) with the loss of one hydrochloric species and one chloridion. This can be further mineralized into m/z values of 362, which followed via the cleavage of $C-N(CH_3)_2$ forming intermediate with m/z values of 318. Then the byproducts could be degraded into possible intermediates with m/z values of 163, 167, 247 and 274 through the carboxylation, ring-opening reaction and so on. Subsequently, the intermediates were further oxidized into 2-methylbenzoic acid, benzoic acid, methyl acetate other molecules. According to the intermediates identified, the proposed degradation intermediates and reaction pathways of CTC were exhibited Fig. 6b. Moreover, the mineralization degree of CTC was examined by TOC analyzer during the degradation process. The TOC removal ratio gradually increased with the irradiation time was prolonged. The maximum TOC removal of CTC reached 76.39% after 80 min.

Additionally, the photocatalytic activity was also investigated for TC. As we anticipated, comparing with pure Co_2SnO_4 and Co_2SnO_4 - SnO_2 , Co_2SnO_4 - SnO_2 /GC also exhibited a superior degradation effect for TC once the reaction system was exposed to visible light irradiation (Fig. 5c). The removal efficiency achieved nearly 80% after 80 min.





Scheme 2. Schematic of the mechanisms for the different reactions over the Co_2SnO_4 - SnO_2/GC heterojunction.

3.2.2. Catalytic reduction activity

The typical catalytic reaction of chemical reduction of p-NP by NaBH₄ was chosen to further evaluate the catalytic property of Co₂SnO₄-SnO₂/GC. As shown in Fig. 7a, the Co₂SnO₄-SnO₂/GC also exhibited more prominent catalytic performance compared with Co₂SnO₄ and Co₂SnO₄/SnO₂. The adsorption peak of p-NP solution around at 400 nm gradually dropped in intensity after adding of the catalyst with the proceeding of the reduction reaction, accompanying a new peak around at 300 nm due to the conversion of p-NP into p-AP (inset of Fig. 7a) [57]. The degree of the reduction was also presented by the ratio of C/C_0 . Complete conversion of p-NP to p-AP is obtained about 10 min. As Fig. 7b displayed, the reduction over Co₂SnO₄-SnO₂/ GC composite follows the pseudo first-order kinetics. The k value was estimated to be 0.351 min⁻¹, which is over 3.1 and 2.3 times higher than that of Co_2SnO_4 (0.115 min⁻¹) and Co_2SnO_4/SnO_2 (0.155 min⁻¹). The experimental results can well explain the excellent activity of Co₂SnO₄-SnO₂/GC composite for the reduction of p-NP with NaBH₄.

3.3. Stability

Additionally, the stability of the catalysts was evaluated via a cycle experiment using Co₂SnO₄-SnO₂/GC composite. For each recycling test, Co₂SnO₄-SnO₂/GC was collected by centrifugation, and then washed with deionized water and ethanol for three times, respectively. As displayed in Fig. 8a, it is found that the catalytic performance of Co₂SnO₄-SnO₂/GC is hardly variation after testing more than four

times. As shown in Fig. 8b, the XRD analyses of the Co₂SnO₄-SnO₂/GC hybrid material were carried out before and after the catalytic reactions. Clearly, the main XRD peaks of the recycled Co₂SnO₄-SnO₂/GC have no obvious change. Therefore, the as-prepared Co₂SnO₄-SnO₂/GC hybrid material can be considered to be a stable and efficient catalyst.

3.4. Potential mechanism

The mechanism of GC to inhibit the recombination rate of photoinduced electron-hole pairs can be illustrated by the energy band-gap model of Scheme 2a. Co₂SnO₄ possess a narrow band gap (1.75 eV, Fig. 4b), hence under visible light irradiation, the electrons in the E_{VB} of Co₂SnO₄ would be excited into the conduction band and then injected into the more positive E_{CB} of SnO₂, therefore, the photogenerated electrons and holes of Co2SnO4 can be separated effectively by the n-n junctions formed between the n-type Co₂SnO₄ and n-type SnO₂ interface, and the recombination of electron-hole pairs can be substantially retarded. It is well known that the good conductivity of GC promises fast electronic transmission between the semiconductors and GC. Hence, the electrons on E_{CB} of SnO₂ can be quickly transferred to GC instead of remain in SnO2 lattice, which further facilitates charges separation in SnO₂, which can lower the recombination of photoinduced and enhance the reaction rate in the photocatalytic process. Subsequently, residual holes within the Co_2SnO_4 E_{VB} may directly photooxidize CTC/TC. This conclusion was also supported by the active species trapping experiments (inset of Scheme 2a). Photooxidation by holes appears the primary pathway for CTC/TC degradation. It should be pointed out that the appearance of the special featured GC tends to facilitate the photocatalytic process. Furthermore, the highest photoactivity of Co₂SnO₄-SnO₂/GC could be derived from the synergetic effect, including the porous structure, high light absorbance and the favorable heterojuction structure.

On the other hand, the plausible mechanism for the reduction of *p*-NP is proposed (Scheme 2b). When Co₂SnO₄-SnO₂/GC was added into the mixed solution of *p*-NP and NaBH₄, the BH₄⁻ and *p*-NP ions were easy adsorbed on the surface of Co₂SnO₄-SnO₂/GC. Subsequently, the NaBH₄ as an electron donor reacts with the Co₂SnO₄ component in the hybrid and transfers surface hydrogen species and electrons to them, and then flow to *p*-NP. Therefore, the catalysts act as a medium to transfer electrons from BH₄⁻ to *p*-NP resulting in the formation of p-AP [58,59]. The multiple intimate interfaces of Co₂SnO₄-SnO₂-GC assure rapid transmission of electrons; furthermore, the suitable GC coating increases of the adsorption capability for contaminant. Meanwhile, the cube hollow structure provides sufficient active sites, which is very favorable for the catalytic reaction [60]. That is, there exists a beneficial effect of coating Co₂SnO₄-SnO₂ by GC and their synergetic effects in the Co₂SnO₄-SnO₂/GC hybrid.

4. Conclusions

In summary, Co₂SnO₄-SnO₂ were successfully prepared via calcining CoSn(OH)6 and then subsequently used in the construction of Co₂SnO₄-SnO₂/GC composites with graphene-coated. Co₂SnO₄-SnO₂/ GC heterojunctions were designed as a highly efficient multifunctional catalyzer for photocatalytic and catalytic reduction reaction exhibited superior catalytic activity and high catalytic efficiency, which could be attributed to in situ generated SnO2, which increases the transfer interfaces (Co₂SnO₄-SnO₂-GC). Moreover, the synergetic effect of 2D GC nanosheets, which provides abundant exposed adsorption and reaction sites, high catalytic surface area and excellent electron shuttling from excited semiconductor to reaction sites which facilitates the charge transfer across Co₂SnO₄-SnO₂-GC heterojunction to catalytic reaction, the enhanced structural stability and reusability may also be due to the GC protective layer for Co₂SnO₄-SnO₂. This synthetic conception presents a new effective approach to prepare multifunctional catalysts to achieve environmental remediation.

Acknowledgements

This work was financially supported by the National Nature Science Foundation of China (No. NSFC51672116).

References

- [1] A. Molinari, E. Sarti, N. Marchetti, L. Pasti, Appl. Catal. B: Environ. 203 (2017) 9–17.
- [2] Z. Dong, X. Le, C. Dong, W. Zhang, X. Li, J. Ma, Appl. Catal. B: Environ. 162 (2015) 372–380
- [3] T.R. Mandlimath, B. Gopal, J. Mol. Catal. A: Chem. 350 (2011) 9-15.
- [4] Y. Fan, W. Ma, D. Han, S. Gan, X. Dong, L. Niu, Adv. Mater. 27 (2015) 3767–3773.
- [5] C. Chen, W. Ma, J. Zhao, ChemInform 42 (2011) 4206-4219.
- [6] A. Bera, A.D. Sheikh, M.A. Haque, R. Bose, E. Alarousu, O.F. Mohammed, T. Wu, ACS Appl. Mater. Interfaces 7 (2015) 28404–28411.
- [7] M.B. Ali, F. Barka-Bouaifel, H. Elhouichet, B. Sieber, A. Addad, L. Boussekey, M. Férid, R. Boukherroub, J. Colloid Interface Sci. 457 (2015) 360–369.
- [8] H. Zhang, F. Ke, Y. Li, L. Wang, C. Liu, Y. Zeng, M. Yao, Y. Han, Y. Ma, C. Gao, Sci. Rep. 5 (2015) 14417.
- [9] S.S. Mali, S.S. Chang, K.H. Chang, Sci. Rep. 5 (2015) 11424.
- [10] S.S. Shin, W.S. Yang, J.H. Noh, J.H. Suk, N.J. Jeon, J.H. Park, S.K. Ju, W.M. Seong, I.S. Sang, Nat. Commun. 6 (2015) 7410.
- [11] B.S. Joo, Y.J. Chang, L. Moreschini, A. Bostwick, E. Rotenberg, M. Han, Curr. Appl. Phys. 17 (2017).
- [12] S.S. Shin, E.J. Yeom, W.S. Yang, S. Hur, M.G. Kim, J. Im, J. Seo, J.H. Noh, S.I. Seok, Science 356 (2017) 167–171.
- [13] N. Rajamanickam, P. Soundarrajan, V.K. Vendra, J.B. Jasinski, M.K. Sunkara, K. Ramachandran, Phys. Chem. Chem. Phys. 18 (2016) 8468–8478.
- [14] L. Zhu, Z. Shao, J. Ye, X. Zhang, X. Pan, S. Dai, Chem. Commun. 52 (2015) 970-973.
- [15] A. Marikutsa, M. Rumyantseva, A. Baranchikov, A. Gaskov, Materials 8 (2015) 6437–6454.
- [16] D. Liu, S. Ren, X. Ma, C. Liu, L. Wu, W. Li, J. Zhang, L. Feng, RSC Adv. 7 (2017) 8295–8302.
- [17] M.B. Ali, A. Barras, A. Addad, B. Sieber, H. Elhouichet, M. Férid, S. Szunerits, R. Boukherroub, Phys. Chem. Chem. Phys. 19 (2017) 6569–6578.
- [18] M.B. Ali, A. Hamdi, H. Elhouichet, B. Sieber, A. Addad, Y. Coffinier, L. Boussekey, M. Férid, S. Szunerits, R. Boukherroub, RSC Adv. 6 (2017).
- [19] A.M. Ben, H.H. Yolcu, H. Elhouichet, B. Sieber, A. Addad, L. Boussekey, M. Moreau, M. Férid, S. Szunerits, R. Boukherroub, J. Colloid Interface Sci. 473 (2016) 66–77.
- [20] L. Li, L. Gu, L. Zheng, Z. Fan, G. Shen, ACS Nano 11 (2017) 4067–4076.
- [21] Y.J. Hong, Y.C. Kang, Nanoscale 7 (2015) 701.
- [22] R. Zhang, Y. He, A. Li, L. Xu, Nanoscale 6 (2014) 14221–14226.
- [23] G. Wang, Z.Y. Liu, P. Liu, Electrochim. Acta 56 (2011) 9515–9519.
- [24] B. An, Q. Ru, S. Hu, X. Song, J. Li, Mater. Res. Bull. 60 (2014) 640-647.
- [25] Z. Wang, Z. Wang, W. Liu, W. Xiao, X.W. Lou, Energy Environ. Sci. 6 (2012) 87–91.
- [26] G. Wang, X.P. Gao, P.W. Shen, J. Power Sources 192 (2009) 719–723.
- [27] H. Bouchaaba, B. Bellal, R. Maachi, M. Trari, N. Nasrallah, A. Mellah, J. Taiwan Inst. Chem. Eng. 58 (2016) 310–317.
 [28] H. Wang, J. Zhang, Z. Chen, J. Hu, S. Li, Z. Wang, J. Liu, X. Wang, Chem. Soc. Rev.
- [28] H. Wang, L. Zhang, Z. Chen, J. Hu, S. Li, Z. Wang, J. Liu, X. Wang, Chem. Soc. Rev. 43 (2014) 5234–5244.
- [29] A. Shamirian, M. Edrisi, M. Naderi, J. Mater. Eng. Perform. 22 (2013) 306–311.

- [30] L. Yang, J. Huang, L. Shi, L. Cao, W. Zhou, K. Chang, X. Meng, G. Liu, Y. Jie, J. Ye, Nano Energy 36 (2017).
- [31] X.J. Wen, C.G. Niu, L. Zhang, G. Zeng, ACS Sustai. Chem. Eng. 5 (2017).
- [32] L. Jing, Y. Xu, S. Huang, M. Xie, M. He, H. Xu, H. Li, Q. Zhang, Appl. Catal. B: Environ. 199 (2016) 11–22.
- [33] X. Yang, F. Qian, G. Zou, M. Li, J. Lu, Y. Li, M. Bao, Appl. Catal. B: Environ. 193 (2016) 22–35.
- [34] S. Kumar, A. Baruah, S. Tonda, B. Kumar, V. Shanker, B. Sreedhar, Nanoscale 6 (2014) 4830.
- [35] J.A. Aguilar-Martínez, M.I. Pech-Canul, M. Esneider, A. Toxqui, S. Shaji, Mater. Lett. 78 (2012) 28–31.
- [36] C. Ma, W. Zhang, Y.S. He, Q. Gong, H. Che, Z.F. Ma, Nanoscale 8 (2016) 4121.[37] J. Wang, H. Li, S. Meng, L. Zhang, X. Fu, S. Chen, Appl. Catal. B: Environ. 200
- (2016) 19–30.
- [38] A. Zhao, J. Masa, W. Xia, A. Maljusch, M. Willinger, G. Clavel, K. Xie, R. Schlögl, W. Schuhmann, M. Muhler, J. Am. Chem. Soc. 136 (2014) 7551–7554.
- [39] W. Kang, Y. Tang, W. Li, Z. Li, X. Yang, J. Xu, C.S. Lee, Nanoscale 6 (2014) 6551.
- [40] Z.Q. Liu, H. Cheng, N. Li, T.Y. Ma, Y.Z. Su, Adv. Mater. 28 (2016).
- [41] F. Song, H. Su, J. Chen, W.J. Moon, W.M. Lau, D. Zhang, J. Mater. Chem. 22 (2011) 1121–1126.
- [42] S. Joshi, S.J. Ippolito, M.V. Sunkara, RSC Adv. 6 (2016).
- [43] Y.D. Wang, C.L. Ma, X.D. Sun, Nanotechnology 13 (2002) 565.
- [44] Y. Chen, F. Sun, Z. Huang, H. Chen, Z. Zhuang, Z. Pan, J. Long, F. Gu, Appl. Catal. B: Environ. 215 (2017) 8–17.
- [45] S. Yuvaraj, S. Amaresh, Y.S. Lee, R.K. Selvan, RSC Adv. 4 (2014) 6407-6416.
- [46] L. Su, Y. Xu, J. Xie, L. Wang, Y. Wang, ACS Appl. Mater. Interfaces 8 (2016) 35172–35179.
- [47] J. Yin, Y. Li, F. Lv, M. Lu, K. Sun, W. Wang, L. Wang, F. Cheng, Y. Li, P. Xi, Adv. Mater. (2017) 29.
- [48] F. Lei, Y. Sun, K. Liu, S. Gao, L. Liang, B. Pan, Y. Xie, J. Am. Chem. Soc. 136 (2014) 6826–6829.
- [49] J. Bao, X. Zhang, B. Fan, J. Zhang, M. Zhou, W. Yang, X. Hu, H. Wang, B. Pan, Y. Xie, Angew. Chem. 54 (2015) 7399–74404.
- [50] R. Shi, Z. Li, H. Yu, L. Shang, C. Zhou, W. Gin, L.Z. Wu, T. Zhang, ChemSusChem 10 (2017) 4650–4656.
- [51] A. Akhundi, A. Habibiyangjeh, Mater. Express 5 (2015).
- [52] W. Zou, Y. Shao, Y. Pu, Y. Luo, J. Sun, K. Ma, C. Tang, F. Gao, L. Dong, Appl. Catal. B: Environ. 218 (2017) 51–59.
- [53] F. Chen, Q. Yang, X. Li, G. Zeng, D. Wang, C. Niu, J. Zhao, H. An, T. Xie, Y. Deng, Appl. Catal. B: Environ. 200 (2017) 330–342.
- [54] S. Yang, Y. Gong, J. Zhang, L. Zhan, L. Ma, Z. Fang, R. Vajtai, X. Wang, P.M. Ajayan, Adv. Mater. 25 (2013) 2452–2456.
- [55] J. Yang, D. Chen, Y. Zhu, Y. Zhang, Y. Zhu, Appl. Catal. B: Environ. 205 (2016).
- [56] H. Huang, K. Xiao, T. Zhang, F. Dong, Y. Zhang, Appl. Catal. B: Environ. 203 (2017) 879–888.
- [57] F. Wang, S. Song, K. Li, J. Li, J. Pan, S. Yao, X. Ge, J. Feng, X. Wang, H. Zhang, Adv. Mater. 28 (2016) 10679–10683.
- [58] C. Huang, W. Ye, Q. Liu, X. Qiu, ACS Appl. Mater. Interfaces 6 (2014) 14469–14476.
- [59] Y. Guo, L. Zhang, X. LIU, B. Li, D. Tang, W. Liu, W. Qin, J. Mater. Chem. A 4 (2016) 4044–4055
- [60] J. Wang, A. Tang, L. Tan, H. Yang, J. Ouyang, CrystEngComm 19 (2017) 4824–4831